

CPTH-12 Heat Pump

Optional

Ion Generation

Total Positive/Negative Ion Output

>350M ions/cc/sec

Optional HEPA Kit

HEPA Certified 99.97% @0.3 micron Filtration

Cooling Capacity

Btu/hr

11,500

Operating Range: Min-Max F°

65°-95°

Heating Capacity

Btu/hr

10,300

Operating Range: Min-Max F°

40°-80°

Dimensions

Width (Inches)

19

Depth (Inches)

26.5

Height (Inches)

41.7

Weight (Pounds)

165

Electrical

Specifications

Power Supply (Volts)

115

Current Consumption (Amps)

11.5

Fuse Size (Amps)

15

Plug Configuration

5-15

Voltage (Min-Max)

105-125

Power Cord Length (Feet)

8

Fan

Characteristics

Evaporator:

Air Flow (CFM) High/Low

470/400

Condenser:

Air Flow (CFM) High/Low

1005/888

Compressor

Specifications

Compressor Type

Rotary

Refrigerant Type

R-32

Safety Devices

Compressor Overcurrent Protection

Yes

Fan Motor Protection

Yes

Anti-Freeze Thermostat

Yes

Fan Mode Switch

Yes

Automatic Restart

Yes

Automatic Tank Shut Off

Yes

Audible Condensate Shut Off Alarm

Yes

Built In Safety Switch for Condensate Pump

Yes

Condensate Tank Capacity (Gal)

4.9

LED Control Panel with Timer

Yes

UL2998 Certified Ozone Free

Yes



ClimaTemp

Portables

www.Clima-Temp.com

1-844-349-5665